

主要特点 Main Features

小型继电器适用于电子控制设备、家用电器、办公自动化、试验测试、保安、商用机械、通用设备、汽车、机床、建筑、运输设备、仪器仪表，可作为遥控中间转换或放大原件。

Relay is suitable for small electronic control equipment, household appliances, office automation, test, security and commercial machinery, general equipment, automobile, Machine tools, construction, transportation equipment, instruments and meters, can be used as a remote control center conversion or enlarge the original.

规格型号 Type and Specification



触点形式 Contact form	2H、2D、2Z
触点负载 The contact load	5A/240VAC 28VDC
线圈功率 Coil power	DC:0.9W, AC:1.2VA
线圈规格 Coil specification	DC:6V-220V AC:6V-380V
外形尺寸 Overall dimensions	27×21×35mm



触点形式 Contact form	2H、2D、2Z
触点负载 The contact load	10A/240VAC 28VDC
线圈功率 Coil power	DC:0.9W, AC:1.2VA
线圈规格 Coil specification	DC:6V-220V AC:6V-380V
外形尺寸 Overall dimensions	27×21×35mm



触点形式 Contact form	3H、3D、3Z
触点负载 The contact load	5A/240VAC 28VDC
线圈功率 Coil power	DC:0.9W, AC:1.2VA
线圈规格 Coil specification	DC:6V-220V AC:6V-380V
外形尺寸 Overall dimensions	27×21×35mm



触点形式 Contact form	3H、3D、3Z
触点负载 The contact load	10A/240VAC 28VDC
线圈功率 Coil power	DC:0.9W, AC:1.2VA
线圈规格 Coil specification	DC:6V-220V AC:6V-380V
外形尺寸 Overall dimensions	27.5×31×35mm



触点形式 Contact form	4H、4D、4Z
触点负载 The contact load	3A/240VAC 28VDC
线圈功率 Coil power	DC:0.9W, AC:1.2VA
线圈规格 Coil specification	DC:6V-220V AC:6V-380V
外形尺寸 Overall dimensions	27×21×35mm



触点形式 Contact form	4H、4D、4Z
触点负载 The contact load	10A/240VAC 28VDC
线圈功率 Coil power	DC:1.5W, AC:3.0VA
线圈规格 Coil specification	DC:6V-220V AC:6V-380V
外形尺寸 Overall dimensions	27.5×41×35mm

主要特点 Main Features

小型继电器适用于电子控制设备、家用电器、办公自动化、试验测试、保安、商用机械、通用设备、汽车、机床、建筑、运输设备、仪器仪表，可作为遥控中间转换或放大原件。

Relay is suitable for small electronic control equipment, household appliances, office automation, test, security and commercial machinery, general equipment, automobile, Machine tools, construction, transportation equipment, instruments and meters, can be used as a remote control center conversion or enlarge the original.

规格型号 Type and Specification



JQX-13F-2Z(LY2)

触点形式 Contact form	2H、2D、2Z
触点负载 The contact load	10A/240VAC 28VDC
线圈功率 Coil power	DC:0.9W, AC:1.2VA
线圈规格 Coil specification	DC:6V-220V AC:6V-380V
外形尺寸 Overall dimensions	27×21×35mm



JQX-10F

触点形式 Contact form	2H、2D、2Z, 3H、3D、3Z
触点负载 The contact load	10A/240VAC 28VDC
线圈功率 Coil power	DC:1.8W, AC:2.7VA
线圈规格 Coil specification	DC:6V-220V AC:6V-380V
外形尺寸 Overall dimensions	35×35×53mm



JQX-13F-3Z(LY3)

触点形式 Contact form	3H、3D、3Z
触点负载 The contact load	10A/240VAC 28VDC
线圈功率 Coil power	DC:0.9W, AC:1.2VA
线圈规格 Coil specification	DC:6V-220V AC:6V-380V
外形尺寸 Overall dimensions	27.5×31×35mm



MK2P-1

触点形式 Contact form	2H、2D、2Z
触点负载 The contact load	10A/250VAC 28VDC
线圈功率 Coil power	DC:2W, AC:3.5VA
线圈规格 Coil specification	DC:5V-220V AC:6V-380V
外形尺寸 Overall dimensions	35×35×53mm



JQX-13F-4Z(LY4)

触点形式 Contact form	4H、4D、4Z
触点负载 The contact load	10A/240VAC 28VDC
线圈功率 Coil power	DC:1.5W, AC:3.0VA
线圈规格 Coil specification	DC:6V-220V AC:6V-380V
外形尺寸 Overall dimensions	27.5×41×35mm



MK3P-1

触点形式 Contact form	3H、3D、3Z
触点负载 The contact load	10A/250VAC 28VDC
线圈功率 Coil power	DC:2W, AC:3.5VA
线圈规格 Coil specification	DC:5V-220V AC:6V-380V
外形尺寸 Overall dimensions	35×35×53mm